

Hot Water Heater

Kerosene Burner



**A rugged,
dependable heater
with the highest fuel
efficiency ratings in
the industry.**

KEROSENE HOT WATER HEATER SPECIFICATIONS

MODEL	300	310	350	360	400	410	500
Burner, Oil Pressure Atomizing, Electronic Ignition	Kerosene, #1, #2 Diesel, 315,000 BTU	Kerosene, #1, #2 Diesel, 315,000 BTU	Kerosene, #1, #2 Diesel, 364,000 BTU	Kerosene, #1, #2 Diesel, 364,000 BTU	Kerosene, #1, #2 Diesel, 434,000 BTU	Kerosene, #1, #2 Diesel, 434,000 BTU	Kerosene, #1, #2 Diesel, 560,000 BTU
Burner, Gas Natural Aspirating	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Fuel Consumption	2.25 GPH	2.25 GPH	2.6 GPH	2.6 GPH	3.1 GPH	3.1 GPH	4 GPH
Fuel Tank Capacity	12 Gal.	12 Gal.	9 Gal.	9 Gal.	Optional	Optional	Optional
Coil** (Steel Pipe)	126, 5/8" ID Schedule 80	126, 1/2" ID Schedule 80	126, 5/8" ID Schedule 80	126, 1/2" ID. Schedule 80	168, 5/8" ID Schedule 80	168, 1/2" ID Schedule 80	250, 5/8" ID Schedule 80
Wheels	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	Stationary	Stationary	Stationary
Dimensions	37" L, 16" W, 25" H	37" L, 16" W, 25" H	56" L, 27" W, 26" H	56" L, 27" W, 26" H	22" L, 22" W, 50" H	22" L, 22" W, 50" H	22" L, 22" W, 50" H
Weight	200 LBS	270 LBS	235 LBS	300 LBS	260 LBS	300 LBS	375 LBS
Temperature Control	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Flow Switch	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Flow Oil Solenoid	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Electronic Ignition	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Oil Primary Control	Optional	Optional	Optional	Optional	Optional	Optional	Optional

MODEL	510	750	760	1000	1010	1050	1060
Burner, Oil Pressure Atomizing, Electronic Ignition	Kerosene, #1, #2 Diesel, 560,000 BTU	Kerosene, #1, #2 Diesel, 630,000 BTU	Kerosene, #1, #2 Diesel, 630,000 BTU	Kerosene, #1, #2 Diesel, 1,000,000 BTU	Kerosene, #1, #2 Diesel, 1,000,000 BTU	Kerosene, #1, #2 Diesel, 1,400,000 BTU	Kerosene, #1, #2 Diesel, 1,400,000 BTU
Burner, Gas Natural Aspirating	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Fuel Consumption	4 GPH	4.5 GPH	4.5 GPH	6.7 GPH	6.7 GPH	10 GPH	10 GPH
Fuel Tank Capacity	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Coil** (Steel Pipe)	250, 5/8" ID Schedule 80	420, 5/8" ID Schedule 80	420, 1/2" ID Schedule 80	483, 3/4" ID Schedule 80	483, 3/4" ID Schedule 80	483, 3/4" ID Schedule 80	483, 3/4" ID Schedule 80
Wheels	Stationary	Stationary	Stationary	Stationary	Stationary	Stationary	Stationary
Dimensions	22" L, 22" W, 50" H	30" L, 24" W, 60" H	30" L, 24" W, 60" H	36" L, 30" W, 60" H	36" L, 30" W, 64" H	36" L, 30" W, 64" H	36" L, 30" W, 64" H
Weight	425 LBS	475 LBS	525 LBS	625 LBS	675 LBS	625 LBS	675 LBS
Temperature Control	Optional	Standard	Standard	Standard	Standard	Standard	Standard
Flow Switch	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Flow Oil Solenoid	Optional	Standard	Standard	Optional	Optional	Optional	Optional
Electronic Ignition	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Oil Primary Control	Optional	Standard	Standard	Standard	Standard	Standard	Standard

Note: Water heaters are not a stock item. Allow 2 to 4 weeks delivery time.
 **ADTM A-53 steel pipe, spiral wound, cold water wrap design, removable.



Alcester, South Dakota 57001
 1.800.255.6823 fax 1.800.325.5682
 www.alkota.com

