

### makes a difference





## FOR FAST CLEAN-UPS, ANY TIME.

Electric broom designed for daily use.



# For fast and efficient sweeping.

Whisper-quiet electric broom for discrete and quick interim cleaning. Features Ni-Cad battery technology allows for long operating times - 30 minutes on carpets and up to 45 minutes on hard surfaces. Designed for commercial-duty, the EB 30/1 is durable and ergonomic. Includes one battery and charger.



#### Convenient interim cleaning

- Equipped with a powerful quickchange battery, the EB 30/1 can be used anywhere
- Whisper quiet.
- Ergonomically designed for commercial use..
- 30 minute run times.



#### Easily empty debris

- The EB 30/1 has a large capacity dustpan for coarse and fine debris and is easily removed for emptying.
- Designed with a universal joint to allow the handle to be locked or unlocked.



#### <sup>3</sup> Brush replacement without tools

The roller brush can be removed without tools for easier cleaning.

## Technical data and equipment.

	EB 30/1
Technical data	
Working width	12" (300 mm)
Container capacity	.26 gallon (1 l)
Noise level	56 dBA
Operating time (carpet/hard surface)	30 min / 45 min
Battery charging time	12 hrs
Weight	5 lbs (2.3 kg)
Dimensions (L x W x H)	9.8" x 11.8" x 43.3" (250 mm x 300 mm x 1100 mm)

Equipment		
Product	Order No.	Description
EB 30/1	1.545-121.0	12" Ni-Cad battery-operated sweeper

Accessories				
	Order No.	Description		
	4.654-259.0	Ni-Cad battery		
	6.646-670.0	Battery charger		
	4.762-400.0	Replacement Roller Brush, Packaged		
	4.762-401.0	Roller Brush, Red, For Hard Surfaces		
	6.654-197.0	Rechargeable battery charger - For charging Kärcher rechargeable battery packs Ni-Cad, NiMH and Li-Ion type		

■ Included □ Optional

Please contact us for more information:

#### **North America**

4555 Airport Way Denver, CO 80239 U.S.A. Phone 800-456-6649 Fax 303-738-2818

www.karcher.com/us

#### Canada

6535 Millcreek Drive Unit 67 Mississauga, ON L5N 2M2 Canada Phone 905-672-8233 Fax 905-672-3155

www.karcher.ca