# LANDA®

### **Industrial Pressure Washers** ....Built Right to Do the Job Right

TR

## Customized, Trailer-Mounted Hot Water Pressure Washer System

■ 330-gallon white High-Density Polyethylene

- Single or Tandem Axle
- Customized Hot-Water Pressure Washer
- 200 or 330 Gallon Water Tank
- Many Accessories

Wheel and axle assembly features an Industrial Undercarriage leaf-spring suspension of up to 3,500 lbs. per axle and 14-inch, white spoke wheels (shown with optional chrome wheels and fenders).

Water Tank (200-gallon for TR-3500 model) comes standard with the trailer and features a 12-inch access port plus a 11/2-inch drain valve, 3/4inch float valve and a 50-mesh inlet strainer.

Made of durable 14 gauge steel, Optional Tool Box and Extra Fuel Tank doubles as a generous tool storage with safety hold-open lid, and a 50-gallon tank for extra fuel; includes standard 2<sup>1</sup>/<sub>4</sub>-inch gas tank filler opening; slosh-proof baffled reservoir; gasoline outlet is above gas line; 2-inch NPT opening for a transfer pump (not included) to pump fuel to either the equipment or other vehicles.



Shown with pressure washer and options. Tool box shown is no longer available on this unit.

Dual-axle or single-axle trailers come with standard Electric Brakes with Break Away Kit or optional hydraulic breaks.

Two 3-way ball valves make it easy to Switch Water Sources from the holding tank to direct water feed from a hose faucet.

Durable Steel Cage holds the water tank and features a pressure washer wand holder for quick and ready cleaning accessibility.

Made of extra-durable 2-by-3 inch structural tubing and covered with a powder-coated epoxy black finish for weather protection; this Heavy-Duty Chassis features lighted license plate holder and recessed tail lights; all electrical wiring is recessed within the tubular frame.

The Optional Hose Reel (not shown) holds up to 150 ft. of hose and quick connects to chassis.



Made to handle up to 1,500 lbs (1,000 lbs on the TR-3500), the swivel jack Trailer Tongue Assembly, with a 2-inch or 2 5/6-inch ball coupler for quick and easy hook up of the trailer. Dual %-inch chains are also included for additional safety.



## LANDA<sup>®</sup> TR

## WHY CHOOSE THE TR TRAILER?

We have made customizing a trailer-mounted wash system for on-site cleaning as easy as 1-2-3.

Step 1: Choose from two rugged trailer configurations-the dual-axle TR-6000 or the single-axle TR-3500.

Step 2: Select from five series of portable, self-contained, industrial-grade, hot-water pressure washers, any of which can be mounted on either trailer (except the SLT).

Step 3: Add any of our many options and accessories, such as hose reels, chrome coverings, etc., to enhance the performance.

Both trailers are made of extra-rugged 2-by-3 inch structural tubing. The wheel and axle assembly feature leaf-spring suspension of up to 3,500 lbs. per axle and 14-inch, white spoke wheels. A powder-coated epoxy finish gives the entire package added weather protection.



TR-3500 Single Axle Trailer Shown with pressure washer and optional chemical rack



TR Hot-Water Pressure Washer Selection						
PDHW	PGHW	PGDC				
4 Models Available	4 Models Available	3 Models Available				
4.7 GPM	3.5 - 4.8 GPM	3.8 - 4.7 GPM				
3500 PSI	3000 - 4000 PSI	3500 PSI				
Diesel	Gasoline	Gasoline				
TR-6000	TR-6000	TR-6000				
TR-3500	TR-3500	TR-3500				
GVWR (Ibs)	Water Tank	Ship Wt (lbs)				
3500	200 gal	720				

Model #	Part #	Axle	GVWR (lbs)	Water Tank	Ship Wt (lbs)
TR-3500	1.103-801.0	Single	3500	200 gal	720
TR-6000	1.103-804.0	Tandem	6000	330 gal	1080

Dimensions: TR-3500 130"L x 73"W x 58"H TR-6000 178"L x 80"W x 62"H

#### **Field Installed Options & Accessories**

Hose Reel Kits (Hose Not Included) 8.902-448.0 Hose Reel Kit (200' capacity, 3/8" high-pressure hose) • 8.917-262.0 Mounting & Plumbing Kit for PGHW4-30324E • 8.902-449.0 Hose Reel Kit (100' capacity, 3/4" garden hose) +

#### Wheels and Fenders

• Factory Installed

Distributed by:

8.902-466.0 Chrome Wheels Upgrade (per pair) +

8.902-468.0 Chrome Fender Assembly for Tandem Axle Upgrade (per pair) \*\*

8.902-467.0 Chrome Fender Assembly for Single Axle Upgrade (per pair) •

\* TR-3500 Only

#### **Mounting Kits**

8.902-447.0 Hose Reel Kit (100' capacity,3/8" high-pressure hose) • 8.917-264.0 Mounting & Plumbing Kit for PGHW5-35324E, PGHW4-40324E • 8.917-263.0 Mounting & Plumbing Kit for PGHW5-30224E • 8.920-435.0 Mounting & Plumbing Kit for PDHW5-35624E + 8.902-456.0 Mounting & Plumbing for PGDC +

#### Brakes

8.902-441.0 Hydraulic Brake Kit (single axle, 2" ball hitch) • \* 8.902-442.0 Hydraulic Brake Kit (single axle, 3" lunette eye) • \* 8.902-438.0 Hydraulic Brake Kit (two axles, 2-5/6" ball hitch) + \*\* 8.902-452.0 Hydraulic Brake Kit (two axles, 3" lunette eye) • \*\*

#### Signage Plate

8.902-469.0 Signage Plate •

#### **Chemical Rack**

8.912-409.0 2-5 gal. Bucket Chemical Rack • \*\* **Hitch Couplers** 

#### 8.924-493.0 2-5/6" Ball Hitch Coupler • \*

8.902-436.0 3" Lunette Eye Hitch Coupler • \*

8.902-471.0 3" Lunette Eye Hitch Coupler • \*\*

\*\* TR-6000 Only

## **DETERGENT FOR EVERY JOB**

Landa's innovative detergent lineup makes your cleaning job easier and faster. Phosphate-free to meet the most stringent environmental demands without sacrificing cleaning effectiveness. We'll match you with a product designed for your specific application.



Note: Landa is constantly improving and updating its products. Consequently, pictures, features, and specifications in this brochure may differ slightly from current models. Flow rates and pressure ratings may vary due to variances allowed by manufacturers of our machine components. Landa product performance is certified by the Cleaning Equipment Trade Association (CETA) to be within 5% of listed specifications