

LANDA®

Industrial Pressure Washers
...Built Right to Do the Job Right

TRV-3500

Customized, Trailer-Mounted
Hot Water Pressure Washer System

- Single Axle
- Customized Hot-Water Pressure Washer
- 3,000 lb Load Capacity
- 200 Gallon Water Tank
- Swing-Away Tongue

■ 200-gallon white **High-Density Polyethylene Water Tank** comes standard with the trailer and features a 7-inch access port plus a 2-inch drain plug, ¾-inch float valve, and a 50-mesh outlet filter.

■ **Optional Hose Reels** hold up to 150 ft. of high-pressure hose and quick connects to chassis.

■ Made of extra-durable 2-by-4 inch, 10-gauge formed channel, and covered with a powder-coated epoxy black finish for weather protection; this **Heavy-Duty Chassis** features recessed lights with all electrical wiring recessed within the frame.

■ The single-axle trailer comes with standard **Electric Brakes with Break Away Kit** or optional hydraulic brakes.



■ **Innovative Dual Drain System.** Primary drain for easy daily use purposes. Secondary drain allows tank to be emptied when winterizing the unit.

■ Made to handle up to 1,000 lbs, the swivel jack **Trailer Tongue Assembly**, with a 2-inch ball coupler for quick and easy hookup of the trailer. Two ½-inch chains are also included for additional safety.

TRV-3500 Trailer
Shown with pressure washer and options



■ 3-way ball valve makes it easy to **Switch Water Sources** from the holding tank to direct water feed from a hose faucet.

■ **Wheel and axle assembly** features an **Industrial Undercarriage** leaf-spring suspension of up to 3,000 lbs. with 15-inch, white rimmed wheels and sturdy fenders.

■ Made of durable 14 gauge steel, **Optional Rear-Mount Utility Rack** and **Side Saddle Boxes** provide generous tool storage.



■ **Durable Swing-Away Tongue** (rated for 3,500 lbs) allows trailer to be stored in smaller area.

www.landa.com

WHY CHOOSE THE TRV TRAILER?

Landa has made customizing a trailer-mounted wash system for on-site cleaning an easy two-step process.

Step 1: Select from five series of portable, self-contained, industrial-grade, hot-water pressure washers.

Step 2: Add any options and accessories, such as hose reels, rear utility rack, side saddle tool boxes, etc. to enhance the performance.

The TRV-3500 trailer is made of extra-rugged 2-by-4 inch, 10-gauge formed channel. The wheel and axle assembly feature leaf-spring suspension of up to 3,500 lbs. and 15-inch, white rimmed wheels. A powder-coated epoxy finish gives the entire package added weather protection.



TRV Hot-Water Pressure Washer Selection



PDHW
4 Models Available
4.7 GPM
3500 PSI
Diesel
Belt Drive Pump
948-998 lbs



PGHW
4 Models Available
3.5-4.8 GPM
3000-4000 PSI
Gasoline
Belt Drive Pump
725-1285 lbs



PGDC
3 Models Available
3.8-4.7 GPM
3500 PSI
Gasoline
Belt Drive Pump
630-697 lbs

Model #	Part #	Axle	GVWR (lbs)	Water Tank	Ship Wt (lbs)
TRV-3500	1.103-820.0	Single	3000	200 gal	1072

Dimensions: 136"L x 66"W x 52"H

Field Installed Options & Accessories

Mounting Kits

- 8.920-434.0 PDHW Mounting Assembly •
- 8.917-299.0 PGHW Mounting Assembly •*
- 8.917-399.0 PGDC Mounting Assembly •

Brakes

- 8.917-398.0 Hydraulic Brakes •

Wheels

- 8.917-583.0 Wheel Kit (2 chrome wheels)

Hose Reel Kits (Hose Not Included)

- 8.917-554.0 High Pressure Hose Reel (100' capacity) •
- 8.917-555.0 Low Pressure Hose Reel (100' capacity) •

Hitch Couplers

- 8.924-493.0 2-5/16" Ball Hitch Coupler •
- 8.924-368.0 3" Lunette Eye Hitch Coupler •

Utility Rack

- 8.917-560.0 Utility Rack (rated for up to 150 lbs)

Battery

- 8.904-051.0 Battery installed on pressure washer •

Saddle Boxes

- 8.917-558.0 Saddle Box (each)
- 8.917-556.0 Saddle Boxes (2 boxes) •

Rock Guards

- 8.917-557.0 Rock Guard •
- 8.917-559.0 Rock Guard

• Factory Installed * PGHW5-50524E Not Compatible

Distributed by:

DETERGENT FOR EVERY JOB

Landa's innovative detergent lineup makes your cleaning job easier and faster. Phosphate-free to meet the most stringent environmental demands without sacrificing cleaning effectiveness. We'll match you with a product designed for your specific application.

